

# GETAC

Semi Rugged Rugged **Fully Rugged** Ultra Rugged



GETAC recommends Windows Vista® Business

# E100

## Tablet PC

- Sunlight readable display  
Optional 800 Nits with Touch Screen
- Light Weight
- MIL-STD 810F and IP 54 Compliance
- Shock-mounted HDD
- Full Magnesium Alloy Case



Rugged Mobile Computing Solutions  
**BUILT TO SURVIVE**

www.ruggednotebooks.nl

# E100



# E100 Ultra Portable Tablet PC

## SPECIFICATIONS

<b>Ruggedness</b>	Full magnesium alloy case Shock-mounted HDD Vibration & drop-shock resistant Optional sunlight readable display Light weight and multi radio MIL-STD 810F and IP54 compliance
<b>CPU</b>	Intel® A110 800MHz 400 MHz FSB 512KB L2 cache
<b>Memory</b>	512MB, up to 1GB
<b>VGA Controller</b>	Intel 945GU with integrated Gen 3.5 Core Graphic
<b>Display</b>	8.4" TFT SVGA transmissive display (800x600) Touch screen
<b>Sunlight Readable Display</b>	Optional 800 nits with touch screen
<b>Storage</b>	PATA 60GB/80GB/100GB
<b>Keyboard</b>	Numeric keys with backlight
<b>Expansion Slot</b>	PCMCIA Type II x 1
<b>Smart Card reader</b>	Smart Card reader x 1
<b>Communication Interface</b>	10/100/1000 base-T Ethernet WLAN 802.11b/g Optional GPS (with internal antenna and pass through) Bluetooth (V2.0+EDR class 2) Optional EV-DO/GSM/GPRS/EDGE/UMTS/WCDMA/HSDPA and pass through
<b>Security</b>	TPM 1.2 Kensington lock
<b>Power</b>	AC Adapter (50W, 100-240V, 50/60Hz) Li-Ion battery (5200mAh) Optional add-on 2nd Li-Ion battery (7800mAh)
<b>Dimensions &amp; Weight</b>	280mm x 184mm x 32mm, 1.4kg
<b>Operating System</b>	Microsoft® Windows® XP Professional Microsoft® Windows® Vista Compatible
<b>Environmental Specification</b>	Operating Temp: 0° to 60°C (-20°C Optional) Storage Temp: -40° to 75°C Humidity: 5% to 95% RH, non-condensing

\*Specifications subject to change without notice.

GETAC recommends Windows Vista® Business



### Bottom

DC in x 1  
Dock Connector x 1  
GPS and WWAN antenna pass through x 2



### Leftside

Network (RJ-45) x 1  
USB 2.0 x 2



### Top

Smart Card Reader x 1  
PC Card/Express Card slot x 1  
Audio Output x 1

## ACCESSORIES

Secondary battery (available in Q2'08)  
Vehicle dock with port replicator and power cable  
Carrying bag  
Vehicle adapter (90Watts, 12-32V)

**GETAC US**  
20762 Linear Lane,  
Lake Forest, CA 92630, USA  
TEL: +1-949-699-2888  
Toll Free: +1-866-GO-GETAC  
(1-866-464-3822)  
<http://www.getac.com>

**GETAC EUROPE**  
Nedge Hill  
Telford TF3 3AH, UK  
TEL: +44 1952 207 231

**GETAC ASIA-PACIFIC**  
9F, No. 75,  
Ming-Sheng East Rd., Sec. 3,  
Taipei, Taiwan, R.O.C.  
TEL: +886-2-2501-8231

**SALES CONTACT**

- North America:  
Ruggedsales@getac.com
- South America:  
SouthAmericasales@getac.com
- EMEA:  
EMEAsales@getac.com
- APEC:  
APECsales@getac.com
- OEM/ODM:  
ODM.sales@getac.com

**BENELUX SALES CONTACT**  
Fieldworks Direct  
Veemarktkade 8  
NL-5222 AE Den Bosch  
t. +31 (0) 73 624 1111  
f. +31 (0) 73 624 1112  
e. [info@fieldworks.nl](mailto:info@fieldworks.nl)  
w. <http://www.fieldworks.nl>

Support:  
[support@fieldworks.nl](mailto:support@fieldworks.nl)